

Safety Data Sheet

C & W Lure Epoxy Komp A

Replaces date: 07/03/2017

Revision date: 08/04/2020

Version: 2.0.2

SECTION 1: Identification of the substance/preparation and of the company/undertaking

1.1. Product identifier

Trade name: C & W Lure Epoxy Komp A

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended uses: Mainly used for: sealing

1.3. Details of the supplier of the safety data sheet

Manufacturer

Company: Nils Malmgren AB
Address: Box 2039
Zip code: 442 02
City: Ytterby
Country: SWEDEN
E-mail: info@nilsmalmgren.se
Phone: +46 (0)303-93610
Fax: +46 (0)303-92855
Homepage: <http://www.nilsmalmgren.se>
Contact person: Name: Jonny Augustsson, Phone: +46 (0)303 93610, E-mail: jonny@nilsmalmgren.se

Distributor

Company: Wolfcreek Lures AB
Address: Östertorpsvägen 30
Zip code: 832 94
City: ORRVIKEN
Country: SWEDEN
E-mail: info@wolfcreeklures.com
Phone: 0704-328290
Homepage: www.wolfcreeklures.com
Contact person: Name: Anders Ulvforsen, Phone: 0704-328290

1.4. Emergency Telephone Number

+46 (0)704-328290 (Wolfcreek Lures)
112 or Local emergency number

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

CLP-classification: Skin Irrit. 2;H315 Skin Sens. 1;H317 Eye Irrit. 2;H319 Aquatic Chronic 2;H411

Most serious harmful effects: Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Toxic to aquatic life with long lasting effects.

2.2. Label elements

Pictograms

Safety Data Sheet

C & W Lure Epoxy Komp A

Replaces date: 07/03/2017

Revision date: 08/04/2020

Version: 2.0.2



Signal word: Warning

Contains

Substance: Epoxy Novolac; 1,4-bis(2,3 epoxypropoxy)butane; Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight \leq 700)

H-phrases

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H411 Toxic to aquatic life with long lasting effects.

P-phrases

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P273 Avoid release to the environment.
P302+352 IF ON SKIN: Wash with plenty of soap and water.
P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P501 Dispose of contents/container in accordance with local regulation.

2.3. Other hazards

When mixing two components, consult the safety data sheets for both components.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

| Substance | CAS No | EC No | REACH Reg. No. | Concentration | Notes | CLP-classification |
|---|------------|-----------|-----------------------|---------------|-------|--|
| Epoxy Novolac | 9003-36-5 | 500-006-8 | 01-2119454392-40-0003 | 60 - 100% | | Skin Irrit. 2;H315 Skin Sens. 1;H317 Aquatic Chronic 2;H411 |
| Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight \leq 700) | 25068-38-6 | 500-033-5 | | 5 - 10% | | Skin Irrit. 2;H315 Skin Sens. 1;H317 Eye Irrit. 2;H319 Aquatic Chronic 2;H411 |
| 1,4-bis(2,3 epoxypropoxy) butane | 2425-79-8 | 219-371-7 | 01-2119494060-45-0004 | 5 - 10% | | Acute Tox. 4;H312 Skin Irrit. 2;H315 Skin Sens. 1;H317 Eye Irrit. 2;H319 Acute Tox. 4;H332 |

Please see section 16 for the full text of H-phrases.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation: Seek fresh air. Seek medical advice in case of persistent discomfort.

Ingestion: Wash out mouth thoroughly and drink 1-2 glasses of water in small sips. Do not induce vomiting. Seek medical advice in case of persistent discomfort.

Skin contact: Wash skin with soap and water. Do not use organic solvents. Take off contaminated clothing and wash before reuse. Seek medical advice in case of persistent discomfort.

Safety Data Sheet

C & W Lure Epoxy Komp A

Replaces date: 07/03/2017

Revision date: 08/04/2020

Version: 2.0.2

Eye contact: Flush immediately with water (preferably using eye wash equipment) for at least 5 minutes. Open eye wide. Remove any contact lenses. Seek medical advice. If the hardener has been mixed in, rinse the eye with water immediately and get medical attention immediately. Continue to rinse.

General: Eye wash facilities must be available when handling this product.

4.2. Most important symptoms and effects, both acute and delayed

Contact with the skin may cause irritation and allergic contact eczema.

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

Suitable extinguishing media: Extinguish with powder, foam, carbon dioxide or water mist.

Unsuitable extinguishing media: Do not use water stream, as it may spread the fire.

5.2. Special hazards arising from the substance or mixture

Not flammable, but can sustain combustion. Hazardous fumes are formed in fire conditions. Carbon monoxide and carbon dioxide.

5.3. Advice for fire-fighters

Firefighters exposed to combustion gases/decomposition products should use a respiratory protective device.

Other Information: Notify proper authorities in case of contamination of soil or aquatic environment or discharge to drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel: Keep unnecessary people away, isolate hazard area and deny entry. Wear suitable protective clothing. Wear safety goggles if there is a risk of eye splash.

6.2. Environmental precautions

Prevent spillage from entering drains and/or surface water. Notify proper authorities in case of contamination of soil or aquatic environment or discharge to drains.

6.3. Methods and material for containment and cleaning up

Contain and absorb spill with sand or other absorbent material and transfer to suitable waste containers.

6.4. Reference to other sections

See section 8 for information on exposure controls and personal protection. See section 7 for handling and storage. See section 13 for waste treatment methods.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Containers should be kept tightly closed. Avoid contact with skin and eyes. All work must be carried out under well-ventilated conditions. Wash hands before breaks, before using restroom facilities, and at the end of work. Do not eat, drink or smoke during work.

7.2. Conditions for safe storage, including any incompatibilities

Safety Data Sheet

C & W Lure Epoxy Komp A

Replaces date: 07/03/2017

Revision date: 08/04/2020
Version: 2.0.2

Keep in tightly closed original packaging. Store in a dry, cool, well-ventilated area.

7.3. Specific end use(s)

Polymerise together with part B during heat emission. Wear suitable protective clothing.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit: Contains no substances subject to reporting requirements

Legal basis: Not known for the mixture.

8.2. Exposure controls

Personal protective equipment, eye/face protection: Wear safety goggles/face protection. Eye protection must conform to EN 166.

Personal protective equipment, skin protection: Wear suitable protective clothing.

Personal protective equipment, hand protection: Wear gloves. Type of material: Nitrile rubber/ Butyl rubber. Penetration time of glove material: 3 hours. We have reduced the penetration time by a factor of 3, when the test standard EN 374-3 is done at 23°C, while the temperature inside the glove is approx. 35°C. In addition, the elastic material extends during use, thereby glove thickness and penetration time is reduced. Recommended thickness of the glove is ≥ 0.4 mm. Selection of the suitable gloves does not only depend on the material, but also on quality and these will vary between manufacturers.

Personal protective equipment, respiratory protection: When grinding not completely cured product, use special gas cartridge A / P3 (organic substances / especially fine dust).

Other Information: Wash hands before breaks, before using restroom facilities, and at the end of work. Take off contaminated clothing and wash before reuse.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| Parameter | Value/unit |
|----------------------|--|
| State | Liquid |
| Colour | Light yellow |
| Odour | Weak |
| Solubility | Miscible with the following: Organic solvents. |
| Explosive properties | No data |
| Oxidising properties | No data |

| Parameter | Value/unit | Remarks |
|---|------------|-----------|
| pH (solution for use) | No data | |
| pH (concentrate) | No data | |
| Melting point | No data | |
| Freezing point | No data | |
| Initial boiling point and boiling range | > 200 °C | DIN 53171 |
| Flash Point | > 250 °C | ISO 2719 |
| Evaporation rate | No data | |
| Flammability (solid, gas) | No data | |
| Flammability limits | No data | |
| Explosion limits | No data | |
| Vapour pressure | < 0.1 hPa | 20°C |
| Vapour density | No data | |
| Relative density | No data | |

Safety Data Sheet

C & W Lure Epoxy Komp A

Replaces date: 07/03/2017

Revision date: 08/04/2020

Version: 2.0.2

| | | |
|---------------------------------------|----------|-----------|
| Partition coefficient n-octanol/water | No data | |
| Auto-ignition temperature | 460 °C | DIN 51794 |
| Decomposition temperature | > 200 °C | |
| Viscosity | 1.5 Pas | 25°C |
| Odour threshold | No data | |

9.2 Other information

| Parameter | Value/unit | Remarks |
|-----------|------------------------|---------|
| Density | 1,15 g/cm ³ | 20°C |

Other Information: Solubility in water: Insoluble

SECTION 10: Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

The product is stable when used in accordance with the supplier's directions.

10.3. Possibility of hazardous reactions

May react under considerable heat buildup with amines.

10.4. Conditions to avoid

Avoid contact with the following: Acids/ Oxidisers.

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

Hazardous fumes are formed in fire conditions. Carbon monoxide and carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

Epoxy Novolac, cas-no 9003-36-5

| Organism | Test Type | Exposure time | Value | Conclusion | Test method | Source |
|----------|-----------|---------------|--------------|------------|-------------|--------|
| Rat | LD50 | | > 10000mg/kg | | | |

1,4-bis(2,3 epoxypropoxy)butane, cas-no 2425-79-8

| Organism | Test Type | Exposure time | Value | Conclusion | Test method | Source |
|----------|-----------|---------------|------------|------------|-------------|--------|
| Rat | LD50 | | 1163 mg/kg | | | |

Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700), cas-no 25068-38-6

| Organism | Test Type | Exposure time | Value | Conclusion | Test method | Source |
|----------|-----------|---------------|-------------|------------|-------------|--------|
| Rat | LD50 | | 15000 mg/kg | | | |

May cause slight irritation of the mucous membrane.

Acute toxicity - dermal

Epoxy Novolac, cas-no 9003-36-5

| Organism | Test Type | Exposure time | Value | Conclusion | Test method | Source |
|----------|-----------|---------------|-------------|------------|-------------|--------|
| Rat | LD50 | | > 2000mg/kg | | | |

Safety Data Sheet

C & W Lure Epoxy Komp A

Replaces date: 07/03/2017

Revision date: 08/04/2020

Version: 2.0.2

1,4-bis(2,3 epoxypropoxy)butane, cas-no 2425-79-8

| Organism | Test Type | Exposure time | Value | Conclusion | Test method | Source |
|----------|-----------|---------------|-------------|------------|-------------|--------|
| Rabbit | LD50 | | > 2150mg/kg | | | |

Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700), cas-no 25068-38-6

| Organism | Test Type | Exposure time | Value | Conclusion | Test method | Source |
|----------|-----------|---------------|-------------|------------|-------------|--------|
| Rabbit | LD50 | | 23000 mg/kg | | | |

May cause reddening and sensitization or other allergic response.

Acute toxicity - inhalation: Inhalation of spray mist is irritating to the upper airways.

Skin corrosion/irritation: May cause sensitisation by skin contact.

Serious eye damage/eye irritation: May cause eye irritation.

Respiratory sensitisation or skin sensitisation: May cause sensitisation by skin contact.

SECTION 12: Ecological information

12.1. Toxicity

Epoxy Novolac, cas-no 9003-36-5

| Organism | Species | Exposure time | Test Type | Value | Conclusion | Test method | Source |
|-----------|----------------|---------------|-----------|-----------|------------|-------------|--------|
| Crustacea | Daphnia magna | 48h | LC50 | 2.55 mg/l | | | |
| Algae | | 72h | LC50 | 1.8 mg/l | | | |
| Fish | Leuciscus idus | 96h | EC50 | 2.54 mg/l | | | |

1,4-bis(2,3 epoxypropoxy)butane, cas-no 2425-79-8

| Organism | Species | Exposure time | Test Type | Value | Conclusion | Test method | Source |
|---------------|------------|---------------|-----------|-----------|------------|-------------|--------|
| Acute fish | Zebra-fish | 96h | LC50 | 19.8 mg/l | | | |
| Acute Daphnia | | 24h | EC50 | 75 mg/l | | | |

Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700), cas-no 25068-38-6

| Organism | Species | Exposure time | Test Type | Value | Conclusion | Test method | Source |
|-----------|----------------|---------------|-----------|----------|------------|-------------|--------|
| Fish | Leuciscus idus | 96h | LC50 | 2 mg/l | | | |
| Crustacea | Daphnia magna | 48h | EC50 | 1.8 mg/l | | | |
| Algae | | 72h | EC50 | 11 mg/l | | | |

No results from ecotoxicological tests are available. Ecotoxicological information only related to components.

12.2. Persistence and degradability

Not readily degradable.

12.3. Bioaccumulative potential

Test data are not available.

12.4. Mobility in soil

Test data are not available.

12.5. Results of PBT and vPvB assessment

Not applicable

Safety Data Sheet

C & W Lure Epoxy Komp A

Replaces date: 07/03/2017

Revision date: 08/04/2020

Version: 2.0.2

12.6. Other adverse effects

Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Destruction according to local regulations.

Disposal methods: May be disposed of by mixing with the right amount of hardener.

Contaminated packaging: Put the empty container up-side-down. Use a tool to completely empty the container. Sort the waste according to local regulations.

Category of waste: 08 01 11* waste paint and varnish containing organic solvents or other hazardous substances
15 01 10* packaging containing residues of or contaminated by hazardous substances

SECTION 14: Transport information

Land transport (ADR/RID)

| | | | |
|--|---|-------------------------------------|---|
| 14.1. UN-No.: | 3082 | 14.4. Packing group: | III |
| 14.2. UN proper shipping name: | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Novolac) | 14.5. Environmental hazards: | The product must be labelled as an environmental hazard (symbol: fish and tree) in packaging sizes of more than 5 kg/l. |
| 14.3. Transport hazard class(es): | 9 | | |
| Hazard label(s): | 9 | | |
| Hazard identification number: | 90 | Tunnel restriction code: | - |

Inland water ways transport (ADN)

| | | | |
|--|---|-------------------------------------|---|
| 14.1. UN-No.: | 3082 | 14.4. Packing group: | III |
| 14.2. UN proper shipping name: | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Novolac) | 14.5. Environmental hazards: | The product must be labelled as an environmental hazard (symbol: fish and tree) in packaging sizes of more than 5 kg/l. |
| 14.3. Transport hazard class(es): | 9 | | |
| Hazard label(s): | 9 | | |
| Transport in tank vessels: | | | |

Sea transport (IMDG)

| | | | |
|--|---|---|---|
| 14.1. UN-No.: | 3082 | 14.4. Packing group: | III |
| 14.2. UN proper shipping name: | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Novolac) | 14.5. Environmental hazards: | The product must be labelled as a Marine Pollutant (MP) in packaging sizes of more than 5 kg/l. |
| 14.3. Transport hazard class(es): | 9 | Environmental Hazardous Substance Name(s): | |
| Hazard label(s): | 9 | | |
| EmS: | F-A, S-F | IMDG Code segregation group: | - None - |

Safety Data Sheet

C & W Lure Epoxy Komp A

Replaces date: 07/03/2017

Revision date: 08/04/2020
Version: 2.0.2

Air transport (ICAO-TI / IATA-DGR)

| | | | |
|--|---|-------------------------------------|---|
| 14.1. UN-No.: | 3082 | 14.4. Packing group: | III |
| 14.2. UN proper shipping name: | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Novolac) | 14.5. Environmental hazards: | The product must be labelled as an environmental hazard (symbol: fish and tree) in packaging sizes of more than 5 kg/l. |
| 14.3. Transport hazard class(es): | 9 | | |
| Hazard label(s): | 9 | | |

14.6. Special precautions for user

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Special Provisions: This product is assessed and classified in accordance with the requirements of the European Parliament and Council Regulation (EC) No 1272/2008 and subsequent amendments.

15.2. Chemical Safety Assessment

SECTION 16: Other information

Version history and indication of changes

| Version | Revision date | Responsible | Changes |
|---------|---------------|------------------|---------|
| 2.0.2 | 08/04/2020 | Nils Malmgren AB | Update |
| 2.0.1 | 07/03/2017 | Nils Malmgren AB | Pt 3 |

Abbreviations: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)IMDG: International Maritime Code for Dangerous GoodsIATA: International Air Transport AssociationIATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)ICAO: International Civil Aviation OrganizationICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)GHS: Globally Harmonized System of Classification and Labelling of ChemicalsEINECS: European Inventory of Existing Commercial Chemical SubstancesCAS: Chemical Abstracts Service (division of the American Chemical Society)DNEL: Derived No-Effect Level (REACH)PNEC: Predicted No-Effect Concentration (REACH)LC50: Lethal concentration, 50 percentLD50: Lethal dose, 50 percent

Other Information: The information contained herein is based on the best of our knowledge and shall describe our product under the aspect of safety. They are not meant to guarantee specific properties of the product. Recipients of our product must take responsibility for observing existing laws and regulations.

Classification method: Calculation based on the hazards of the known components.

List of relevant H-statements

| | |
|------|--------------------------------------|
| H312 | Harmful in contact with skin. |
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |

Safety Data Sheet

C & W Lure Epoxy Komp A

Replaces date: 07/03/2017

Revision date: 08/04/2020
Version: 2.0.2

H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H411 Toxic to aquatic life with long lasting effects.

SDS is prepared by

Company: Nils Malmgren AB, Miljöavdelningen
Country: SWEDEN

Document language: GB